

Premium touch screen for your home

The Akuvox S562W-2 multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.



At a Glance

- Ultra-clear, stylish appearance;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Completely solve the stability problem of Wi-Fi with Wi-Fi 6;
- Two-way audio communication with other units in the 2-Wire IP network;
- Powered by NS-2 or external source;
- Super long transmission distance via 2-wire cable;
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

Physical & Power

- | | |
|--|---|
| • Front Panel: Plastic | • 2-Wire Ports: 2 |
| • RAM / ROM: 128MB / 128MB | • Ethernet Ports: 1xRJ45, 10/100Mbps adaptive |
| • Display: 7-inch TFT LCD | • PoE: 802.3af Power-over-Ethernet |
| • Screen: 7-inch capacitive touch screen | • Power: 48V DC Connector (If Not Using NS-2) |
| • Wi-Fi: IEEE802.11 b/g/n/ax, @2.4GHz | • DC 48V Standby Power: ≤4W |
| • RS485 Port: 1 | • DC 48V Full Load Power: ≤9W |
| • Relay Out: 1 | • Installation: Wall-mounted & Desktop |
| • Bell In: 1 | • Dimension: 216.4x118.8x21.7mm |
| • Alarm Inputs: 8 | • Working Humidity: 10~90% |
| • Microphone: 1 | • Working Temperature: -10°C ~ +45°C |
| • Speaker: 1 | • Storage Temperature: -20°C ~ +70°C |

Touch Screen Display

- Display Mode: Normally Black, Transmissive
- LCD Size: 7-inch (Diagonal)
- Resolution: 1024x600
- Contrast Ratio: 300:1
- Luminance: 250 nits
- Viewing Angle: 35° Left, 35° Right,
35° Upper, 35° Lower
- Touch Screen: Projected Capacitive

Audio

- SIP: SIP v1 (RFC 2543) & SIP v2 (RFC 3261)
- Narrowband Audio Codec: PCMU, PCMA, G.729
- Broadband Audio Codec: G.722
- DTMF: Out-of-Band (RFC 2833), SIP INFO
- Echo Cancellation
- Voice Activity Detection
- Comfort Noise Generator
- Automatic Gain Control

Video

- Video Codec: H.264

Networking

- Supported Protocols: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web Management Portal
- Web-based Packet Capture
- Configuration Backup / Restore
- Firmware Upgrade
- System Logs

Application Scenario

- Villas
- Apartment Complexes
- Home Automation Systems
- Modern Interiors