Perfect Doorphone choice for daily life

Akuvox S532 is a video door phone that incorporates a wide-angle camera to provide comprehensive visual coverage. It holds notable IP and IK ratings, ensuring durability and security for the building. Its integrated unique functionality facilitates keyless access for added convenience. Enhance your building's safety with the Akuvox S532, where security and simplicity converge.



At a Glance

- **Vandal resistant body, with numeric keypad;**
- **Linux operation system;**
- **Wide-angle camera: 130º (H), 90º (V);**
- **Two-way audio communication over IP networks with Echo Cancel feature;**
- **Multi-way access feature including: EM/Mifare Card, PIN, & BLE;**
- **Flush-mounted & wall-mounted;**
- **Complies with SIP;**

Physical & Power

- Front panel: Aluminum
- Camera: 2M pixels, automatic lighting
- Display: 2.8 Inch, 320x240
- Numeric keypad with extra buttons
- Infrared (IR) LED: Support
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: 1ch input/output(selectable)
- RS485 port: Support
- Line out: Support
- BLE: Support BT5.0
- RF reader: 13.56MHz&125kHz, NFC (only Android)
- Relays out: 2
- Inputs: 4
- Microphone: 1
- Speaker: 1
- TF card slot: 1
- Reset: Support
- Tamper Alarm： Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3at Power-over-Ethernet
- IP Rating: IP66
- IK Rating: IK08
- Installation: Flush-mounted & Wall-mounted
- Dimension (HxWxD): 301x106x35.8mm
- Working Humidity: 10~90%
- Working Temperature: -40°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C

Akuvox
Open A Smart World

10/F, No.56 Guanri Road, Software Park II，Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akuvox.com

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Broadband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080p
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 130°(H) / 90°(V)
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Multi-way Unlock: EM/Mifare Card, PIN and BLE
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX

Capacity

- User: 10,000
- Contact: 500
- Card: 50,000
- PIN: 10,000

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP,

Card Type

- EM card
- Mifare card
- DesFire card (EV1/EV2/EV3)
- Felica card

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Akuvox
Open A Smart World

10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akuvox.com